



ETA-Danmark A/S
Göteborg Plads 1
DK-2150 Nordhavn
Tel. +45 72 24 59 00
Fax +45 72 24 59 04
Internet www.etadanmark.dk

Authorised and notified according
to Article 29 of the Regulation (EU)
No 305/2011 of the European
Parliament and of the Council of 9
March 2011

MEMBER OF EOTA



European Technical Assessment ETA-21/0774 of 2024/05/02

I General Part

Technical Assessment Body issuing the ETA and designated according to Article 29 of the Regulation (EU) No 305/2011: ETA-Danmark A/S

Trade name of the construction product:

Genbrugssten Re-used bricks

Product family to which the above construction product belongs:

Recycled clay masonry units

Manufacturer:

Genbrugssten ApS
Agdrupvej 3
DK-9700 Brønderslev
Tel +45 69 16 03 77
Internet www.genbrugssten.dk

Manufacturing plant:

Genbrugssten ApS
Agdrupvej 3
DK-9700 Brønderslev

This European Technical Assessment contains:

6 pages including 1 annex which form an integral part of the document

This European Technical Assessment is issued in accordance with Regulation (EU) No 305/2011, on the basis of:

European Assessment Document (EAD) no. EAD 170005-00-0305 for Recycled clay masonry units

This version replaces:

The ETA with the same number issued on 2021-08-25

Translations of this European Technical Assessment in other languages shall fully correspond to the original issued document and should be identified as such.

Communication of this European Technical Assessment, including transmission by electronic means, shall be in full (except the confidential Annexes referred to above). However, partial reproduction may be made, with the written consent of the issuing Technical Assessment Body. Any partial reproduction has to be identified as such.

II SPECIFIC PART OF THE EUROPEAN TECHNICAL ASSESSMENT

1 Technical description of product

Genbrugssten Re-used bricks are recycled clay masonry units, which are derived from de-installation of clay masonry buildings. The masonry units are brought to the manufacturing plant where they are mechanically cleaned, sorted, controlled and packed.

2 Specification of the intended use in accordance with the applicable European Assessment Document (hereinafter EAD)

The recycled clay masonry units are used for protected or unprotected masonry structure (see definitions 3.3 and 3.4 of EN 771-1) e.g. facing and rendered masonry in self-supporting load transferring masonry structures, including external veneer walls, internal linings and partitions.

The installed clay masonry units will contribute to durability of the works by providing enhanced protection from the effect of weathering.

The provisions made in this European technical assessment are based on an assumed working life of the shuttering kit of at least 50 years.

The indications given on the working life cannot be interpreted as a guarantee given by the producer or Assessment Body, but are to be regarded only as a means for choosing the right products in relation to the expected economically reasonable working life of the works.

3 Performance of the product and references to the methods used for its assessment

Characteristic	Assessment of characteristic								
3.2 Safety in case of fire (BWR2)									
Reaction to fire	The Genbrugssten Re-used bricks are classified as class A1 without testing in accordance with EC Delegated Regulation 2016/364/EU and EN 13501-1								
3.3 Hygiene, health and the environment (BWR3)									
Dimensions	The dimensions of the Genbrugssten Re-used bricks are <table><tr><th>Type</th><th>Length mm</th><th>Width mm</th><th>Height mm</th></tr><tr><td>Genbrugssten Re-used bricks</td><td>228</td><td>108</td><td>55</td></tr></table> The tolerance on all dimensions is ± 15 mm corresponding to tolerance category Tm in EN 771-1	Type	Length mm	Width mm	Height mm	Genbrugssten Re-used bricks	228	108	55
Type	Length mm	Width mm	Height mm						
Genbrugssten Re-used bricks	228	108	55						
Density	The gross dry density of Genbrugssten Re-used bricks is 1550 kg/m3 with tolerance class Dm (±30%) in accordance with EN 771-1								
Compression strength	See annex A								
Initial rate of water absorption	No performance assessed								
Bond strength	No performance assessed								
Determination of volume and percentage of voids and net volume	No performance assessed								
Freeze/thaw resistance	No performance assessed								
Active soluble salt content	No performance assessed								

4 Assessment and verification of constancy of performance (hereinafter AVCP) system applied, with reference to its legal base

4.1 AVCP system

According to the decision 97/740/EC of the European Commission, the system(s) of assessment and verification of constancy of performance (see Annex V to Regulation (EU) No 305/2011) is 2+.

5 Technical details necessary for the implementation of the AVCP system, as provided for in the applicable EAD

Technical details necessary for the implementation of the AVCP system are laid down in the control plan deposited at ETA-Danmark prior to CE marking

Issued in Copenhagen on 2024-05-02 by



Thomas Bruun
Managing Director, ETA-Danmark

Annex A

Compressive strength

The value of the compressive strength as the 50% fractile at a 95 % confidence level with uniform, unknown distribution of the bricks is declared to be

Type	Declared value, normalized compressive strength, f_b(MPa)
Genbrugssten Re-used bricks	15

The declared value is the normalized value (f_b) for each product type and is fixed based on mean value, sample standard deviation and lowest single value of the sample, so that:

$$f_b < f \text{ and } f_b < x/0,8$$

where

x is the lowest single value in the test sample

(f) is the lower 50% fractile calculated in relation to the size and distribution of test samples.

Calculation of the normalized compression strength (f_b) is obtained by multiplication of the measured compression strength by a shape factor (d). The shape factor (d) is determined according to EN 772-1:2011+A1:2015(E).

Within the declared dimensions the shape factor (d) is between 0.7 and 1,30. The exact shape factor is either calculated by interpolation or the value 0,7 is used.

Since variations occur in the manufacturing process, the declared value (f_b) is fixed to ensure that the assessed performance is on the safe side.